

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 06-248243

(43)Date of publication of application : 06.09.1994

(51)Int.Cl. C09J 7/02
C09J 7/02

(21)Application number : 05-038173 (71)Applicant : SEKISUI CHEM CO LTD

(22)Date of filing : 26.02.1993 (72)Inventor : SEN TAKUO
SAKAHARA MANABU

(54) ADHESIVE TAPE FOR PHOTOLITHOGRAPHY

(57)Abstract:

PURPOSE: To provide an adhesive tape for photolithography having an adhesive agent layer, on whose surface grooves capable of forming air ducts are disposed, on a transparent substrate, facilitating the removal of air bubbles when an article to be exposed to light is mad to adhere to a mount, giving a beautiful picture after closely contacted and inverted, and preventing the adhesion of the product from being forgot.

CONSTITUTION: The adhesive tape is characterized by comprising a transparent substrate (preferably a film such as polyester or polyethylene) 1 capable of transmitting light having an activity against photosensitive substances and an adhesive agent layer 2 and disposing grooves capable of forming air ducts on the surface of the adhesive agent layer 2. The groove-formed adhesive agent layer is obtained, e.g. by applying an embossed roll having desired groove forms to the surface of the adhesive agent layer 2 formed on the substrate layer 1. The thickness of the substrate is preferably 10-50 μ m, and the depth of the groove is also preferably at least 5 μ m.

